



Zero VOC HiOmega® Stucco

Polar Industries, Inc.
www.polarindustries.net

Based on a rapidly renewable natural epoxy, HiOmega Stucco is a no-odor, zero VOC and environmentally friendly stucco. HiOmega Stucco consists of a primary base adhesive and a finishing adhesive. The primary base adhesive is light weight and easy to apply on an inlay standard mesh*. The finishing adhesive can be trowelled or sprayed on to a surface. Color can be added to the finishing adhesive to match the building project. HiOmega Stucco is water impermeable and yet breathable. The primary base adhesive and the finishing adhesive are eligible for LEEDS points.

*not for use on styrofoam.

No-Odor, Zero VOC HiOmega Stucco

Because it is based on natural epoxy, our HiOmega Stucco is non-toxic and environmentally friendly.



PRIMARY BASE COAT ADHESIVE

- ☒ 2 part system, Part A & B
- ☒ Contains silica
- ☒ Renewable all natural, toughened flexible polyol
- ☒ Light weight
- ☒ Breathable, water impermeable
- ☒ 1 hr to set, 7 days to cure
- ☒ Add 45% Portland Cement, trowel to wall
- ☒ Inlay standard mesh
- ☒ Not for use over styrofoam

FINISH ADHESIVE

- ☒ Contains silica
- ☒ 1 hour to set, 7 day cure
- ☒ Breathable, water impermeable
- ☒ Part A and B- 2 part system
- ☒ Add 30% Portland Cement
- ☒ Light Weight
- ☒ Add color to suit
- ☒ Trowel on or sprayed

For pricing and order information contact us:

Polar Industries, Inc. Box 293, Fisher Branch, Manitoba Canada R0C 0Z0
Tel: (204) 372-8482 Cell: (786) 955-4008 email: polarindustry@yahoo.com