

HiOmega® LINSEED OIL

HiOmega ® linseed oil is a new flax oil with 70 % linolenic C18:3 omega 3 fatty acid. This high linolenic acid content yields superior characteristics wherever a linseed oil is used. For example, HiOmega ® linseed oil may be used raw or boiled as a wood finish or blended with other compounds for a varnish. HiOmega ® linseed oil polymerizes quickly for faster drying and is excellent for alkyd resins in oil based paints. In epoxidized oil

applications, the high linolenic acid content creates a more reactive epoxy for adhesives and coatings. HiOmega ® is available in bulk quantities. All natural and no-VOC, HiOmega ® linseed oil is an environmentally friendly, rapidly renewable resource.

70% Linolenic Acid C18:3

A superior natural oil, our linseed oil is a fast drying base for numerous products.

| Product: HiOmega® Linseed Oil | | |
|-------------------------------|----------------|---------------------|
| Quality Assurance | Typical Result | Limit |
| Appearance | Pass | A Golden Yellow Oil |
| Acid Value | 0.50 mg KOH/g | NMT 5 mg KOH/g |
| Peroxide Value | 4.0 meq/kg | NMT 10 meq/kg |
| Moisture & Volatiles | 0.11% | NMT 0.2% |
| Insoluble Impurities | 0.1% | NMT 0.3% |
| Chemical Residues | 0.0% | NMT 2.0 PPM |

For pricing and order information contact us:

Polar Industries, Inc. Box 293, Fisher Branch, Manitoba Canada R0C 0Z0 Tel: (204) 372-8482 Cell: (786) 955-4008 email: polarindustry@yahoo.com